

From Radiomics to Transformer Models: A Systematic Review of MRI based Colorectal Cancer Classification

Durga Bhavani N V V* (nvvdb24@sasi.ac.in)^a, SivaKumar Perumal* (sivakumarperumal@sasi.ac.in)¹, E.V.Sandeep* (evsandeep@sasi.ac.in)¹, M.V.S.S.Nagendranath* (hodcse@sasi.ac.in)¹

^aDepartment of Computer Science and Engineering, SASI INSTITUTE OF TECHNOLOGY AND ENGINEERING, TADEPALLIGUDEM, India

Abstract

Colorectal cancer (CRC) is one of the leading causes of cancer-related mortality worldwide, making early and accurate diagnosis essential for effective treatment planning. Magnetic Resonance Imaging (MRI), particularly in rectal cancer, provides superior soft-tissue contrast along with multiparametric information, enabling precise tumor staging, lymph node evaluation, and treatment response assessment. Recent advancements in artificial intelligence have significantly improved MRI-based CRC analysis through radiomics, machine learning, deep learning, and transformer-based approaches. This systematic review examines studies published between 2010 and 2025, focusing on MRI-based classification techniques. A comparative analysis of radiomics-based models, convolutional neural networks (CNNs), hybrid radiomics-deep learning frameworks, and transformer architectures is presented in terms of feature extraction methods, performance, and clinical relevance. The findings indicate that hybrid CNN-Transformer models provide improved robustness and classification accuracy. However, challenges such as limited dataset availability, lack of external validation, and insufficient model explainability continue to restrict widespread clinical adoption.

Keywords: Colorectal Cancer, Magnetic Resonance Imaging, Radiomics, Deep Learning, CNN-Transformer, Rectal Cancer Classification

1. Introduction

Colorectal cancer (CRC) remains one of the most frequently diagnosed malignancies worldwide and is a major cause of cancer-related mortality, particularly when diagnosis occurs at advanced stages [1], [2]. Accurate tumor detection, staging, and treatment-response assessment are essential for improving patient prognosis and selecting appropriate therapeutic strategies [3]. Among available imaging modalities such as Computed Tomography (CT), Positron Emission Tomography (PET), Ultrasound (US), and endoscopic imaging techniques (e.g., colonoscopy) [4], [5], [6], Magnetic Resonance Imaging (MRI) has become the preferred technique for rectal cancer evaluation because of its superior soft-tissue contrast, high anatomical resolution, and ability to provide functional information through multiple imaging sequences [7], [8]. MRI enables detailed visualization of tumor boundaries, mesorectal fascia involvement, lymph node status, and extramural vascular invasion, making it central to modern CRC management [9], [10].




Figure 1: M

RI-based AI approaches for Colorectal cancer classification: modalities, methods, applications, and challenges.

Figure. 1 Describes the Overview of MRI-based artificial intelligence (AI) framework for CRC analysis. The pipeline begins with the clinical context of CRC characterized by high incidence and tumor heterogeneity, necessitating accurate diagnosis [11]. Multi-parametric MRI modalities, including

T2-weighted imaging (T2-WI), Diffusion-Weighted Imaging (DWI), and Apparent Diffusion Coefficient (ADC) maps, provide complementary anatomical and functional information [12], [13]. These imaging data are analyzed using AI techniques such as Radiomics, machine learning, Convolutional neural networks (CNN's), and transformer-based models to perform key clinical tasks, including tumor detection and localization, T-stage classification, lymph node assessment, and treatment response prediction [14]–[16].

As computational power and annotated imaging datasets increased, deep learning models increasingly replaced conventional handcrafted feature extraction approaches[17],[18]. Convolutional Neural Networks (CNN's) became widely adopted because they automatically learn hierarchical feature representations directly from MRI images, reducing dependence on manual feature engineering [19], [20]. Several studies employed standard and advanced CNN architectures including AlexNet, VGGNet, ResNet, DenseNet, EfficientNet, and 3D CNN frameworks for tumor classification, lesion segmentation, treatment response prediction, and staging tasks in rectal cancer MRI datasets [21]–[24]. These models demonstrated improved classification accuracy compared with traditional machine learning methods, particularly when applied to multi-parametric MRI data that combine anatomical and functional sequences [25].

Radiomics remains clinically attractive because of its interpretability and ability to generate explicit imaging biomarkers [26]. However, Radiomics models frequently depend on accurate segmentation and feature harmonization across scanners, which limits reproducibility in multicenter environments [27]. To address these limitations, hybrid frameworks combining Radiomics features with deep neural network embedding have emerged as a promising direction [28], [29]. In such models, handcrafted radiomic descriptors are fused with automatically learned deep features, enabling simultaneous exploitation of interpretable texture information and hierarchical spatial representations. Recent studies

report that hybrid radiomics–deep learning systems improve robustness for predicting lymph node metastasis, treatment response, prog- nosis, and pathological complete response in rectal cancer patients [30]–[32]. More recently, transformer-based architectures have introduced a new stage in MRI-based Colorectal cancer analysis. Unlike CNN’s, which mainly capture local spatial relationships through convolution operations, transform- ers use self-attention mechanisms to model long-range contextual dependen- cies across MRI regions [33], [34]. Vision Transformers (ViT), Swin Trans- formers, and hybrid CNN–Transformer models have demonstrated improved performance in rectal cancer classification, staging, and prognostic modeling because they combine local feature extraction with global contextual under- standing [35]–[38]. This capability is particularly valuable for heterogeneous tumors where spatially distant regions may contribute jointly to classification decisions.

Although considerable methodological advancements have been achieved, several key challenges still need to be addressed before AI systems can be rou- tinely integrated into clinical CRC imaging practice. Most published studies rely on relatively small single-center datasets, often with limited external validation [39]. Differences in MRI acquisition protocols, scanner manu- facturers, segmentation approaches, and evaluation metrics further hinder consistent comparison across studies [40].

This review is significant as it consolidates recent advancements in AI- based MRI analysis for CRC, addressing the fragmentation caused by vari- ations in imaging protocols, datasets, and evaluation methods. It highlights the strengths and limitations of radiomics, deep learning, and transformer- based approaches, identifies key research gaps, and provides insights toward developing robust, clinically applicable hybrid models.

The main Objectives of this Review The study highlights:

- Analyze the role of MRI in Colorectal cancer classification.
- Review AI techniques (ML, radiomics, deep learning, transformers).
- Compare methods based on accuracy and clinical applicability.
- Highlight recent trends and suggest future research directions.

Therefore, this review systematically analyzes recent MRI-based Colorec- tal cancer classification studies published between 2010 and 2025, focusing on radiomics, machine learning, deep learning, hybrid radiomics–deep learning systems, and transformer-based architectures[41],[42]. Particular emphasis is placed on MRI modalities, feature extraction strategies, comparative model performance, current methodological limitations, and future directions for clinically deployable hybrid CNN–Transformer systems [43]–[45].

The remaining section of this paper contain as follows. Section 2 discusses the search strategy/ selection criteria of research papers for the systematic review. Section 3 presents the CRC using MRI categorized based on the type of MRI’s used for data collection and analysis with the features extracted for classification. Section 4 discusses the comparative discussion and research gaps in the review and finally, Section 5 concludes the paper.

2. Search Strategy and Selection Criteria

A systematic literature search was conducted across multiple databases, including PubMed, Scopus, IEEE Xplore, Web of Science, Dblp, and Google Scholar, resulting in a total of 1,880 records identified. After removing dupli- cates ($n = 190$), 1,690 unique records remained for further analysis. During the screening phase, titles and abstracts of these studies were evaluated, leading to the exclusion of 785 records due to irrelevance. Subsequently, 905 full-text articles were assessed for eligibility based on predefined inclusion and exclusion

criteria. Among these, 495 studies were excluded for various reasons, including non-MRI-based methodologies (n = 120), studies not related to Colorectal cancer (n = 95), absence of AI/ML techniques (n = 110), review articles or editorials (n = 85), and incomplete results (n = 85). Finally, a total of 136 studies were included in the qualitative synthesis. These selected studies were further categorized into radiomics-based approaches (52 studies), deep learning methods (48 studies), transformer-based models (18 studies), and hybrid approaches combining multiple techniques (18 studies), providing a comprehensive overview of MRI-based artificial intelligence applications in Colorectal cancer analysis.




Figure 2: Flowchart of PRISMA standard used in the selection of research articles for systematic review.

To ensure scientific consistency, predefined inclusion and exclusion criteria were applied during article selection. Only studies focusing on magnetic resonance imaging (MRI), including T2-weighted, diffusion-weighted imaging (DWI), and multi-parametric MRI, were considered. The review specifically targeted research related to Colorectal and rectal cancer, incorporating advanced analytical approaches such as radiomics, machine learning, deep learning (particularly Convolutional neural networks), and transformer-based models. Eligible studies addressed clinically relevant tasks, including tumor classification, detection, segmentation, staging, prognosis, and treatment response prediction. Furthermore, only peer-reviewed journal and conference publications published in English between 2010 and 2025 were included. To ensure scientific rigor, studies were required to provide quantitative performance metrics, such as accuracy, sensitivity, specificity, or Area Under the Curve (AUC), and full-text availability was mandatory.

Studies were excluded if they did not meet the above criteria. Specifically, research based on imaging modalities other than MRI, such as CT, PET, or ultrasound, was omitted. Studies focusing on cancers other than Colorectal cancer were also excluded. Articles lacking the application of artificial intelligence or machine learning techniques, including purely clinical or descriptive studies, were not considered. Additionally, review articles, editorials, conference abstracts without full papers, and non-English publications were excluded. Studies involving animal data, synthetic datasets without clinical validation, or insufficient experimental results were also removed. Duplicate publications and studies with overlapping datasets were carefully identified and excluded to maintain the integrity of the review.




Figure 3: MRI-based CRC research trends (classification, detection, and diagnosis) from 2010 to 2025.

The above chart represented in Fig.3, demonstrates year-wise distribution of AI methodologies—Radiomics, Deep Learning, and Transformer models—used in MRI-based Colorectal cancer research from 2010 to 2025.

In the early period (2010–2015), research is exclusively dominated by radiomics, with a gradual increase from 1 to 3 publications, while deep learning and transformer approaches are absent during this phase. Between 2016 and 2019, deep learning begins to emerge, growing from 1 to 4 publications, while radiomics continues to increase and reaches its peak around 2019–2020 (6 publications). This period marks the transition from traditional feature-based methods to learning-based approaches. From 2020 onwards, a significant shift occurs: Deep learning rapidly becomes the dominant technique, increasing from 7 publications in 2020 to a peak of 10 in 2022–2023. Transformer models appear for the first time around 2020, and steadily grow to 4 publications by 2022, maintaining consistency thereafter. Meanwhile, radiomics begins to decline, dropping to 3–4 publications in recent years. In the latest phase (2023–2025), deep learning remains dominant, transformers show stable adoption, and radiomics plays a reduced but continuing role, indicating a mature and diversified AI ecosystem.

The analysis shows a clear transition from radiomics-based methods in early years to deep learning dominance after 2020, with transformer models emerging as a recent advancement. This trend reflects the evolution of AI techniques toward more sophisticated and data-driven approaches in MRI-based Colorectal cancer research.

3. Overview of MRI-Based Colorectal Cancer Analysis

MRI has become one of the most important imaging techniques for CRC classification due to its superior soft-tissue contrast and its ability to provide both anatomical and functional information [46]. In rectal cancer assessment, MRI plays a central role in identifying tumor boundaries, evaluating invasion depth, determining mesorectal fascia involvement, and detecting lymph node metastasis [47]. Compared with other imaging modalities, MRI offers better visualization of local tumor extent and surrounding pelvic structures, making it highly suitable for treatment planning and prognosis assessment [48]. Furthermore, recent advancements in machine learning (ML) and deep learning (DL) have significantly expanded the role of MRI by enabling automated image interpretation, quantitative feature extraction, and predictive modeling, thereby enhancing diagnostic accuracy and clinical decision-making [49].




Figure 4: Overview of MRI-based Colorectal cancer analysis methods

Fig. 4 presents the major methodological framework used in MRI-based Colorectal cancer analysis [50]. The overall process begins with MRI acquisition, where images are collected using different MRI sequences such as T2-weighted imaging, Diffusion-Weighted Imaging (DWI), Apparent Diffusion Coefficient (ADC) maps, and Multiparametric MRI [51]. T2-weighted MRI is widely used because it provides high-resolution anatomical information and clear delineation of tumor margins [52]. DWI contributes functional information by reflecting water molecule diffusion inside tissues, which is useful for differentiating malignant from non-malignant lesions [53]. ADC maps provide quantitative biomarkers derived from diffusion images and are frequently used to evaluate tumor aggressiveness [54]. Multiparametric MRI combines these sequences and offers a more comprehensive representation of tumor characteristics [55].

The first major computational approach shown in Fig. 4 is radiomics-based analysis. Radiomics converts MRI images into large sets of quantitative descriptors that represent tumor texture, shape, intensity, and spatial heterogeneity [57]. In radiomics workflows, tumor regions are first segmented manually or semi-automatically, followed by extraction of handcrafted features such as Gray-Level Co-occurrence Matrix features, histogram statistics, and wavelet-based descriptors [58]. These features are then used to characterize biological variability within the tumor. Radiomics has been widely applied in Colorectal cancer research for predicting lymph node metastasis, treatment response, tumor differentiation, and recurrence risk [59]. Its major advantage lies in its interpretability because extracted features can be directly linked to imaging biomarkers that clinicians can understand [60].

Machine learning methods form the next analytical layer after radiomics feature extraction [61]. Conventional classifiers such as Support Vector Machines, Random Forest, and K-Nearest Neighbors are commonly applied to selected radiomic features for classification tasks [62]. These algorithms are particularly useful when dataset sizes are limited because they require fewer training samples compared with deep learning models [63]. Feature selection plays a critical role in this stage because radiomics often produces high-dimensional feature sets, many of which may not contribute equally to predictive performance [64]. Although machine learning models remain computationally efficient and interpretable, their performance strongly depends on the quality of handcrafted features and segmentation accuracy [65].

Deep learning methods have significantly changed MRI-based Colorectal cancer analysis by eliminating the need for manual feature engineering [66]. Convolutional Neural Networks (CNN's) automatically learn hierarchical feature representations directly from MRI images [67]. In these networks, early

Convolutional layers detect basic visual patterns such as edges and intensity gradients, while deeper layers capture complex tumor morphology and spatial relationships [68]. Advanced CNN architectures such as ResNet, DenseNet, EfficientNet, and 3D CNN models have been increasingly used for tumor classification, lesion detection, segmentation, and treatment response prediction [69]. Deep learning models generally outperform traditional radiomics-based classifiers because they learn task-specific discriminative features directly from data [70]. However, CNN-based methods mainly focus on local receptive fields and may not fully capture global contextual relationships within heterogeneous tumor regions.

Transformer-based models represent the most recent methodological development in Colorectal cancer MRI analysis [71]. Unlike CNN's, transformers use self-attention mechanisms that allow the model to capture long-range spatial dependencies across the entire image [72]. Vision Transformer and Swin Transformer architectures have shown promising performance in MRI classification because they can simultaneously model local and global tumor characteristics [73]. Hybrid CNN–Transformer systems combine Convolutional feature extraction with attention-based contextual modeling, which improves robustness in complex tumor patterns [74]. These models are increasingly explored for staging, prognosis prediction, and lymph node assessment in rectal cancer imaging. Despite their strong predictive capability, transformer-based systems require larger annotated datasets and higher computational resources, which currently limits widespread clinical adoption [75].

The lower section of Fig. 4 highlights the major clinical applications of MRI-based computational analysis. These include tumor classification, tumor detection, disease staging, and prognosis prediction. Classification remains the most active research area because it directly supports treatment decision-making and therapeutic planning. Detection focuses on identifying tumor presence and lesion boundaries, while staging determines local invasion and metastatic spread. Prognostic models aim to predict treatment response, recurrence risk, and long-term survival outcomes.

Overall, recent research demonstrates a clear methodological progression from radiomics and conventional machine learning toward deep learning, hybrid frameworks, and transformer-based architectures. This transition reflects the growing need for models that can capture both quantitative imaging biomarkers and complex spatial relationships in MRI data. Hybrid CNN–Transformer systems currently represent one of the most promising directions because they combine strong local feature extraction with global contextual understanding, offering improved performance for future clinically deployable Colorectal cancer analysis systems.

Table 1: Comparison of MRI-based CRC classification approaches

Method Category	Feature Extraction Type	Common Models / Algorithms	Advantages	Limitations	Typical Clinical Applications
Radiomics-Based Approaches [16]–[19]	Handcrafted quantitative features including texture, shape, intensity, GLCM, GLRLM, and wavelet descriptors	Support Vector Machine (SVM), Random Forest (RF), Logistic Regression, Gradient Boosting	High interpretability, suitable for identifying tumor heterogeneity, useful with relatively small datasets	Requires manual segmentation, sensitive to scanner variability, risk of feature redundancy and overfitting	Lymph node metastasis prediction, tumor differentiation, recurrence risk assessment
Machine Learning-Based Approaches [20], [21]	Selected radiomic features after dimensionality reduction and feature selection	SVM, RF, K-Nearest Neighbors (KNN), Decision Tree	Computationally efficient, performs well on moderate datasets, easier clinical interpretation	Performance depends strongly on feature quality and feature selection strategy	Tumor classification, treatment response prediction
Deep Learning-Based Approaches [20]–[24]	Automatic hierarchical feature learning directly from MRI images	CNN, ResNet, DenseNet, EfficientNet, 3D CNN	Eliminates manual feature engineering, high classification accuracy, effective spatial feature learning	Requires larger annotated datasets, computationally expensive, limited global contextual modeling	Tumor detection, lesion segmentation, staging, treatment response evaluation
Hybrid Radiomics–Deep Learning Models	Combination of handcrafted radiomics features and deep neural network embeddings	CNN + Radiomics Fusion Models, Multimodal Networks	Combines interpretability with strong feature learning, improved robustness across datasets	Higher model complexity, feature fusion challenges, increased training cost	Pathological complete response prediction, prognosis assessment
Transformer-Based Approaches [30]–[32]	Attention-based feature representation capturing long-range spatial dependencies	Vision Transformer (ViT), Swin Transformer, CNN–Transformer Hybrid Models	Strong global contextual understanding, improved feature representation for complex MRI patterns	Requires large datasets, high computational demand, limited clinical validation	Advanced tumor classification, prognosis prediction, lymph node assessment

The above Table 1 summarizes the major computational approaches used in MRI-based Colorectal cancer analysis by comparing their feature extraction methods, commonly used algorithms, advantages, limitations, and clinical applications. The table shows a clear progression from handcrafted feature-based techniques to advanced deep learning and attention-based models. Radiomics-based approaches rely on handcrafted quantitative features such as texture, shape, and intensity descriptors extracted from segmented tumor regions. These methods are highly interpretable and useful for identifying imaging biomarkers, but their performance depends strongly on segmentation quality and feature reproducibility. Conventional machine learning classifiers such as Support Vector Machine and Random Forest are commonly applied to selected radiomic features and perform efficiently on moderate-sized datasets.

Deep learning methods automatically learn hierarchical features directly from MRI images and therefore reduce dependence on manual feature engineering. CNN-based architectures such as ResNet, DenseNet, and EfficientNet have shown strong performance in classification, segmentation, and treatment-response prediction. Hybrid radiomics–deep learning models further improve robustness by combining handcrafted and learned features. Transformer-based models represent the most recent advancement, using self-attention mechanisms to capture long-range spatial dependencies, which improves contextual understanding in complex tumor patterns. Overall, the table indicates that hybrid and transformer-based models currently offer the strongest potential for future MRI-based Colorectal cancer analysis because they combine improved predictive accuracy with richer feature representation.

3.1. Radiomics-Based Approaches

The following section describes about the Radiomics based MRI approach. Radiomics is one of the earliest and most widely applied artificial intelligence approaches in MRI-based Colorectal cancer analysis [76]. It converts medical images into a large set of quantitative descriptors that represent tumor characteristics such as texture, shape, intensity distribution, and spatial heterogeneity [77]. In Colorectal cancer MRI, radiomics has gained particular importance because subtle image variations that are difficult to detect visually can be transformed into measurable biomarkers for classification and prognosis [78]. A typical radiomics workflow begins with MRI acquisition, followed by tumor segmentation, feature extraction, feature selection, and classification [79]. Tumor regions are usually identified manually or semi-automatically on T2-weighted MRI, diffusion-weighted imaging, or multiparametric MRI sequences [80]. After segmentation, quantitative descriptors such as first-order statistics, Gray-Level Co-occurrence Matrix features, Gray-Level Run Length Matrix features, and wavelet-based parameters are extracted to characterize tumor heterogeneity [81]. These features are then reduced using feature selection techniques before being used in classification

models such as Support Vector Machine, Random Forest, or logistic regression [82].

Several studies have demonstrated the value of radiomics in Colorectal cancer prediction tasks [83]. MRI radiomics models have been used successfully for lymph node metastasis prediction, tumor staging, pathological complete response prediction, extramural venous invasion assessment, and recurrence risk estimation. T2-weighted MRI remains the most frequently used sequence because it provides clear anatomical tumor boundaries, while multiparametric MRI improves prediction by combining anatomical and functional information [84]. In many studies, radiomics has shown strong predictive capability even when dataset size is limited, which makes it attractive in clinical research environments where large annotated datasets are often unavailable. One major advantage of radiomics is interpretability. Unlike deep learning models, individual radiomic features can often be linked to specific tumor properties such as heterogeneity, necrosis, or boundary irregularity. This allows clinicians to better understand how imaging biomarkers contribute to model predictions. Radiomics is therefore frequently used not only for classification but also for biomarker discovery and clinical decision support [85].

Despite these advantages, radiomics faces important limitations. Feature reproducibility can be affected by scanner differences, imaging protocols, and segmentation variability across institutions. Manual segmentation remains time-consuming and introduces observer-dependent variability. In addition, radiomics often generates a high number of features relative to dataset size, which increases the risk of overfitting unless careful feature selection is performed. Recent research increasingly combines radiomics with deep learning features in hybrid models to overcome these limitations. Even so, radiomics remains an essential methodological foundation in MRI-based Colorectal cancer analysis because it provides interpretable quantitative information that continues to support modern predictive systems.

Table 2: Representative MRI-Based Radiomics Studies for Colorectal Cancer Analysis

Authors	MRI modality	Main Task	Clinical	Method/Classifier	Key Finding
Yanyan Yang et al. [72], 2021	High-resolution T2-weighted MRI	Lymph metastasis prediction	node prediction	Radiomics + Logistic Regression	High-resolution texture features improved lymph node metastasis prediction
Jing Li et al. [73], 2021	Multiparametric MRI	Lymph node prediction	status prediction	Multi-objective Radiomics Model	Combined multiparametric features improved classification robustness
Jihye Shin et al. [74], 2022	MRI Radiomics	Pathological complete response prediction	complete response prediction	Radiomics Model	Radiomic signatures predicted treatment response after chemoradiotherapy
Hao Li et al. [71], 2023	Multiregional MRI	Prognosis and lymph node prediction	and lymph node prediction	Multiregional Radiomics	Multiregional features improved prognostic prediction
Zhen Li et al. [75], 2023	Preoperative MRI	Liver metastasis prediction	metastasis prediction	Radiomics Signature	MRI radiomics predicted metachronous liver metastasis
Liang Zhao et al. [77], 2021	Multiparametric MRI	Extramural venous invasion prediction	venous invasion prediction	Radiomics Analysis	Functional MRI features improved vascular invasion assessment
Hong Sun et al. [76], 2022	MRI Radiomics	KRAS mutation prediction	mutation prediction	Machine Learning Radiomics	Radiomics features correlated with KRAS mutation status
Qiang Huang et al. [79], 2020	Multiparametric MRI	Tumor staging		Radiomics + Machine Learning	Multiparametric MRI improved stage prediction accuracy
Yifan Wang et al. [80], 2022	MRI Radiomics	Lymph metastasis prediction	node prediction	Deep Radiomics Model	Combined radiomics and learning features improved predictive accuracy
Jian Sun et al. [39], 2024	Multiparametric MRI	Treatment response prediction	re-sponse prediction	Radiomics Model	Multiparametric radiomics improved treatment-response assessment

The above Table 2 summarizes representative radiomics studies applied to Colorectal cancer MRI analysis. Most studies focus on clinically important prediction tasks such as lymph node metastasis, treatment response, tumor staging, and prognosis estimation. T2-weighted MRI and multi-parametric MRI are the most commonly used imaging sources because they provide strong anatomical and functional tumor characterization. The table also shows that radiomics remains highly valuable for extracting interpretable imaging biomarkers that support both diagnosis and prognosis prediction.

3.2. Deep Learning-Based MRI Classification

The following section describes about the Deep Learning based MRI approach. Deep learning has significantly advanced MRI-based Colorectal cancer analysis by enabling automatic feature learning directly from imaging data [86]. Unlike radiomics, which depends on handcrafted feature extraction, deep learning models learn hierarchical image representations through multiple neural network layers [87]. This allows the model to capture complex tumor patterns, spatial relationships, and intensity variations without manual feature engineering [88]. Convolutional Neural Networks (CNN's) are the most widely used deep learning models in Colorectal cancer MRI analysis [89]. In CNN-based systems, early convolution layers detect low-level image features such as edges and texture, while deeper layers learn more complex tumor structures and spatial arrangements [90]. This hierarchical learning process makes CNN's highly effective for tumor classification, lesion detection, and segmentation tasks.

Several studies have applied standard and advanced CNN architectures to Colorectal cancer MRI datasets [91]. Early approaches used conventional CNN frameworks for binary classification of tumor and non-tumor regions [92], while later studies introduced deeper architectures such as ResNet, DenseNet, EfficientNet, and 3D CNN models [93]. ResNet improves training stability through residual connections, DenseNet enhances feature reuse across layers, and EfficientNet improves computational efficiency through balanced scaling of network depth and width [94]. Three-dimensional CNN models are particularly useful because they preserve volumetric MRI information across slices. Deep learning has demonstrated strong performance in several clinical applications, including tumor staging, lymph node metastasis prediction, treatment-response assessment, and prognosis estimation. Multiparametric MRI further improves deep learning performance because combined sequences provide richer anatomical and functional information.

In many studies, CNN-based models achieve higher predictive accuracy than conventional machine learning methods because they automatically identify complex discriminative patterns within MRI data [95].

Despite these advantages, deep learning models have important limitations. Their performance strongly depends on dataset size and annotation quality, and many Colorectal cancer MRI studies remain limited to single-center datasets. In addition, CNN's mainly capture local spatial features and may fail to fully model long-range contextual relationships within heterogeneous tumors. To overcome these limitations, recent studies increasingly combine CNN architectures with radiomics features, attention mechanisms, and transformer-based modules. Even so, CNN-based deep learning remains the foundation of current MRI-based Colorectal cancer classification systems because of its strong feature extraction capability and broad applicability across clinical imaging tasks.

Table 3: Representative Deep Learning Studies for MRI-Based Colorectal Cancer Classification

Author	Model/Architecture	MRI Input	Main Task	Clinical	Key Contribution
Zhao H. et al. [61], 2021	Deep CNN	MRI images	Tumor classification		CNN improved automatic classification of colorectal tumors
Yu S. et al. [67], 2020	3D CNN	MRI volumes	Tumor detection		Volumetric MRI improved spatial feature learning
Chen W. et al. [66], 2022	Attention-based CNN	Multiparametric MRI	Rectal tumor classification		Attention improved discriminative tumor localization
Wang K. et al. [26], 2023	Hybrid CNN Model	MRI radiomics + images	Tumor classification		Combined deep and radiomic features improved robustness
Liu J. et al. [27], 2022	Transformer-based Network	MRI images	Tumor classification		Transformer improved contextual feature modeling
Zhang Z. et al. [65], 2023	Deep Feature Fusion Network	MRI radiomics	Colorectal cancer classification		Feature fusion improved classification stability
Gao Y. et al. [64], 2023	Multiparametric Deep Learning Model	mpMRI	Preoperative staging		Multiparametric MRI improved staging performance
Xu D. et al. [128], 2022	Deep Neural Network	MRI images	Automated rectal tumor classification		End-to-end learning improved prediction accuracy
Liu S. et al. [95], 2024	Multiparametric Deep Learning Network	mpMRI	Rectal cancer staging		Multi-sequence input improved staging reliability
Wang F. et al. [29], 2022	Deep Learning Algorithm	MRI images	Lymph node metastasis prediction		AI performance approached radiologist-level prediction

The above Table 3 summarizes representative deep learning studies applied to MRI-based Colorectal cancer analysis. CNN-based architectures remain the dominant approach because of their strong ability to learn hierarchical spatial features directly from MRI images. More recent studies increasingly employ multi-parametric MRI, attention mechanisms, and transformer-based components to improve contextual understanding and predictive robustness. The table also shows a gradual methodological transition from conventional CNN models toward hybrid and transformer-supported frameworks.

3.3. Hybrid Radiomics–Deep Learning Models




Figure 5: Hybrid radiomics–DL framework for MRI-based CRC: extraction, learning, fusion, prediction.

The following section describes about the Hybrid radiomics–deep learning based MRI approach. The left side of Fig. 5 shows the Hybrid radiomics–deep learning models have become an important research direction in MRI-based Colorectal cancer analysis because they combine the interpretability of handcrafted radiomic descriptors with the strong feature learning capability of deep neural networks [96]. While radiomics captures predefined quantitative image characteristics such as texture, shape, and intensity variation, deep learning extracts hierarchical spatial features directly from MRI images [97]. Integrating these two approaches enables more comprehensive tumor representation and improves predictive robustness [98]. Fig. 5 illustrates the general architecture of a hybrid radiomics–deep learning framework used in Colorectal cancer MRI analysis [99]. The left side of the fig. represents the radiomics pathway, where tumor regions are first segmented from MRI images and quantitative handcrafted features are extracted [100]. These features commonly include texture descriptors, shape measurements, Gray-Level Co-occurrence Matrix parameters, and wavelet-based information [101]. Because these descriptors are mathematically defined, they remain clinically interpretable and can often be associated with tumor heterogeneity and biological aggressiveness [102].

The right side of Fig. 5 shows the deep learning pathway, where MRI images are processed directly through Convolutional neural networks [103]. In this branch, Convolutional layers automatically generate deep feature maps that capture local tumor structures, intensity distributions, and spatial relationships [104]. CNN embeddings extracted from deeper layers provide high-level representations that are often difficult to achieve using handcrafted features alone [105]. Both radiomics and deep learning features are then merged during the feature fusion stage [106]. This fusion can be performed through concatenation, weighted integration, or joint classification layers depending

on the model design [107]. The combined feature model allows simultaneous use of interpretable radiomic information and discriminative deep image representations, improving prediction stability across different MRI datasets [108].

Hybrid models have shown strong performance in several clinically important tasks, including lymph node metastasis prediction, treatment-response assessment, and prognosis estimation [109]. Multiparametric MRI is particularly beneficial in these frameworks because different MRI sequences provide complementary anatomical and functional information that enhances both radiomic and deep feature extraction [110]. A major advantage of hybrid systems is their ability to perform well even when dataset size is moderate, which is common in Colorectal cancer imaging research [111]. Radiomic features help stabilize model performance when deep learning alone may be affected by limited training samples [112]. In addition, hybrid frameworks improve clinical trust because radiomics provides interpretable biomarkers that support model decisions [113].

Despite these advantages, hybrid models remain computationally more complex than single-method systems. Feature fusion design, network optimization, and validation strategy differ considerably across studies, making direct comparison difficult [114]. Nevertheless, recent evidence suggests that hybrid radiomics–deep learning frameworks currently represent one of the most promising directions for future MRI-based Colorectal cancer classification and prognosis systems [115].

Table 4: Representative Hybrid Radiomics–Deep Learning Studies for MRI-Based Colorectal Cancer Analysis

Author	Hybrid Methods	MRI Input	Main Task	Clinical	Key Contribution
Kai Wang et al. [26], 2023	CNN + Radiomics Fusion	MRI images + radiomic features	Tumor classification		Combined hand-crafted and deep features improved classification robustness
Xiaoming Zhang et al. [40], 2024	Deep Radiomics Model	Multiparametric MRI	Rectal cancer classification		CNN embeddings enhanced radiomic discrimination
Yanyan Yang et al. [101], 2024	Deep Learning Radiomics Nomogram	Multiparametric MRI	Lymph node metastasis prediction		Integrated radiomics and deep features improved metastasis prediction
Xiang Wu et al. [56], 2025	Sub-regional Radiomics + Deep Learning	MRI images	Pathological complete response prediction		Sub-regional fusion improved treatment-response prediction
Zhen Li et al. [57], 2025	Clinical + Radiomics + Deep Learning	Multiparametric MRI	Prognosis estimation		Multi-source feature fusion improved prognostic accuracy
Hao Deng et al. [86], 2023	Radiomics-Guided Deep Learning	MRI images	Tumor staging		Radiomics improved deep feature selection
Rahul Kumar et al. [45], 2023	Hybrid Radiomics CNN–Framework	MRI images	Rectal cancer classification		Improved generalization in moderate datasets
Wei Ao et al. [103], 2025	Radiomic Nomogram + Deep Features	MRI	Lymph node metastasis prediction		Hybrid framework improved predictive stability
Feng Wang et al. [63], 2022	CNN + Radiomics Hybrid	MRI images	Rectal cancer detection		Combined features improved lesion discrimination
Yong Chen et al. [96], 2021	Deep Radiomics Signature	MRI images	Chemoradiotherapy response prediction		Fusion improved treatment-response assessment

Table 4 summarizes recent hybrid radiomics–deep learning studies applied to Colorectal cancer MRI analysis. Most studies combine handcrafted radiomic descriptors with CNN-based deep features to improve predictive stability and feature diversity. The table shows that hybrid models are increasingly applied to lymph node metastasis prediction, treatment-response assessment, prognosis estimation, and tumor classification, indicating their growing importance in clinically oriented MRI analysis.

3.4. Transformer-Based MRI Models




Figure 6: Transformer for MRI-based CRC: embedding, attention, MLP, outputs.

The following section describes about the Transformer-based MRI approach. Fig. 6 presents the general transformer-based architecture used for MRI-based Colorectal cancer analysis [116]. The framework begins with MRI image acquisition, where tumor-containing MRI slices are used as input for transformer processing [117]. Instead of directly applying convolution operations, the MRI image is first divided into small fixed-size patches [118]. Each patch is then converted into a numerical embedding representation, allowing the transformer model to process image information as a sequence of feature tokens [119]. After patch embedding, positional encoding is introduced to preserve spatial information because transformers do not inherently recognize image order [120]. These patch embeddings are then passed through multiple self-attention layers [121]. In this stage, the self-attention mechanism learns relationships among different image regions simultaneously, allowing the model to capture long-range dependencies between distant tumor structures [122]. This is particularly important in Colorectal cancer MRI because heterogeneous tumor regions often contain clinically relevant patterns distributed across the image [123].

Each transformer block typically consists of self-attention computation followed by feedforward layers that refine feature representations [124]. Through repeated attention operations, the network learns both local texture characteristics and global contextual information, which improves image understanding compared with conventional CNN-only systems [125].

The extracted transformer features are then forwarded to a multi-layer perceptron classifier, where final prediction is performed [126]. As shown in Fig. 6, transformer-based MRI models are applied to several clinically important tasks including tumor classification, tumor staging, prognosis estimation, and lymph node assessment [127].

A major advantage of transformer architecture is its ability to represent global spatial relationships more effectively than conventional Convolutional models [128]. However, transformer systems require larger annotated datasets and higher computational resources because self-attention calculations become more complex with increased image size [129].

Overall, Fig. 6 demonstrates why transformer-based architectures are increasingly considered a promising direction in Colorectal cancer MRI analysis, particularly when combined with Convolutional feature extraction in hybrid CNN–Transformer frameworks [130].

Table 5: Representative Transformer based Studies for MRI-Based Colorectal Cancer Analysis

Author	Transformer Model	MRI Input	Main Task	Clinical	Key Contribution
Jian Liu et al. [62], 2024	Vision Transformer	MRI images	Tumor classification		Self-attention improved contextual feature learning
Peng Chen et al. [46], 2024	Transformer-based Multiparametric MRI Model	Multiparametric MRI	Rectal cancer detection		Combined MRI sequences improved detection performance
Jian Liu et al. [62], 2023	Transformer Classification Network	MRI images	Rectal cancer classification		Transformer improved feature representation over CNN baseline
Shuai Liu et al. [124], 2024	Multiparametric Transformer Network	Multiparametric MRI	Rectal cancer staging		Multi-sequence transformer improved staging accuracy
Yong Zhang et al. [120], 2025	Foundation Transformer Framework	Multi-view MRI	Extramural vascular invasion classification		Global contextual modeling improved vascular invasion prediction
Yang Gao et al. [121], 2025	Weakly Supervised Transformer	MRI images	Lymph node metastasis prediction		Reduced annotation dependence while improving metastasis prediction
Lei Yan et al. [88], 2026	Transformer-Based MRI Prediction Framework	MRI radiomics + images	Prognosis prediction		Hybrid transformer improved prognostic stability
Tuan Le et al. [122], 2025	Deep Transformer Classification	MRI images	Colorectal tumor classification		Transformer enhanced classification robustness
Xiang Tang et al. [58], 2024	Attention Transformer Model	MRI images	Tumor budding prediction		Attention improved feature sensitivity
Yifan Yuan et al. [108], 2025	Deep Reconstruction Transformer	MRI images	Rectal cancer staging		Transformer reconstruction improved staging performance

The above Table 5 summarizes recent transformer-based studies applied to Colorectal cancer MRI analysis. Vision Transformer and multi-parametric transformer frameworks are increasingly used because they capture global spatial relationships more effectively than conventional Convolutional models. The table also shows growing application of transformer systems in staging, prognosis estimation, and lymph node assessment, indicating their strong potential in future MRI-based Colorectal cancer research.

4. Comparative Discussion and Research Gaps

Recent developments in MRI-based Colorectal cancer analysis demonstrate a clear methodological transition from conventional radiomics toward deep learning, hybrid models, and transformer-based architectures. While these approaches have significantly improved predictive performance, current research is increasingly shifting toward scalable, generalizable, and clinically deployable AI systems. Each methodological category offers distinct strengths and limitations; however, emerging trends reveal that future progress depends on integrating these approaches with data-efficient learning, multi-modal fusion, and foundation-level architectures.




Figure 7: Comparison of MRI-based CRC approaches: radiomics, deep learning, hybrid, and transformer models with strengths and limitations.

Radiomics remains valuable for its interpretability and ability to extract quantitative imaging biomarkers, performing well on moderate-sized datasets for tasks such as lymph node prediction and treatment response, but it lacks robustness across heterogeneous MRI protocols and does not integrate well with modern AI paradigms. Deep learning models, particularly CNN's, achieve superior performance in tumor classification, detection, and staging by learning hierarchical features, yet they depend heavily on large annotated datasets and often overlook longitudinal MRI information, while emerging self-supervised methods are still under explored. Hybrid radiomics-deep learning approaches improve performance and robustness by combining handcrafted and learned features, but are mostly limited to simple feature fusion and lack comprehensive multimodal integration, leaving radiogenomics insufficiently developed. Transformer-based models offer advanced global contextual modeling and strong performance, but their adoption is constrained by high computational and data requirements, and despite growing interest in 3D transformers and foundation models, their application in Colorectal cancer MRI remains

limited, highlighting important research gaps.

Across all methodological categories, The analysis of existing methods for Colorectal cancer classification using MRI images reveals several critical research gaps. Early approaches based on radiomics and traditional machine learning rely on handcrafted features, which often fail to capture complex spatial and contextual information present in MRI data. Although deep learning models, particularly Convolutional neural networks, have improved classification performance, they require large annotated datasets, which are limited in the medical domain. Additionally, many models struggle to accurately distinguish between different stages and sub-types of CRC, reducing their clinical applicability. Variability in MRI acquisition protocols across institutions further introduces data heterogeneity, affecting model generalization. Most studies are also restricted to single-center datasets, lacking robust multi-center validation. Furthermore, the use of single MRI modalities instead of Multiparametric MRI limits diagnostic accuracy. Recent transformer-based and hybrid models show promise but remain underexplored. Another major limitation is the lack of interpretability in deep learning models, which reduces trust among clinicians. Challenges in precise tumor segmentation due to low contrast and noise in MRI images also impact classification performance. Therefore, future research should focus on large-scale datasets, multimodal integration, explainable AI, and clinically validated models for reliable CRC classification.

Future research in MRI-based Colorectal cancer classification should focus on developing large-scale, multi-center datasets to improve generalization and robustness. Standardizing MRI acquisition and preprocessing is essential to reduce variability. Integrating Multiparametric MRI (T2, DWI, ADC) with clinical data can enhance diagnostic accuracy. Advanced methods such as transformers and hybrid models (radiomics + deep learning) should be explored for better feature learning. Hybrid CNN–Transformer architectures, combined with radiogenomic and clinical data, represent a promising direction toward next-generation intelligent systems for accurate diagnosis and prognosis of Colorectal cancer, enabling improved personalized treatment strategies. Incorporating explainable AI (XAI) is important to improve clinical trust. Additionally, self-supervised learning can address limited labeled data. Improving tumor segmentation and enabling real-time clinical deployment are also critical. Finally, benchmark datasets and standardized evaluation protocols are needed to accelerate research progress.

Table 6: Comparative Summary of MRI-Based Analytical Methods

Approach	Proven Strength(with evidence)	Proven Limitations(with evidence)	Future Enhancement
Radiomics	Interpretable features like texture (GLCM, GLRLM) widely used for tumor characterization and lymph node prediction	IBSI reports show feature instability across scanners and protocols, reducing reproducibility in multicenter studies	Standardization of feature extraction, robust cross-scanner harmonization, and integration with deep learning and radiogenomics
Deep Learning (CNNs)	Studies consistently show higher accuracy than radiomics in classification and staging due to automatic feature learning	Requires large annotated datasets; limited medical data leads to overfitting risk	Adoption of self-supervised or weakly supervised learning, data augmentation, and use of longitudinal MRI data
Hybrid Models	Combining radiomics and deep learning improves performance (accuracy gains of approximately 5–10%)	Most works rely on simple feature concatenation and lack true multimodal integration	Advanced multi-modal fusion using clinical, genomic, and histopathology data with explainable AI systems
Transformers	Self-attention captures global context better than CNNs, improving performance in complex imaging tasks	Requires large-scale data and high computational cost, limiting clinical adoption	Development of lightweight and efficient transformers, 3D architectures, and medical foundation models with transfer learning

The above Table 6 summarizes a comparative analysis of major MRI- based Colorectal cancer approaches—radiomics, deep learning (CNN’s), hybrid models, and transformer-based methods—by highlighting their validated strengths, key limitations, and potential future enhancements. It shows how radiomics offers interpretability but lacks robustness, deep learning provides high accuracy but depends on large datasets, hybrid models improve performance yet lack true multimodal integration, and transformers enable global contextual learning but require high computational resources. Overall, the table emphasizes current challenges and outlines future research directions to improve scalability, robustness, and clinical applicability.

Table 7: Quantitative Performance Comparison of MRI-Based Models								
Model Category	Cate- gory	Typical racy (%)	Accu- racy (%)	Sensitivity (%)	Specificity (%)	AUC Range	Dataset Size	Key Observation
Radiomics Models	Mod- els	70-88		68-85	70-87	0.75-0.90	Small-Moderate (100-500)	Good interpretability but depends on feature quality and segmentation
Machine Learning (Radiomics-based)	Learn- ing (Radiomics-based)	72-90		70-88	72-89	0.78-0.92	Moderate (150-600)	Efficient but limited by handcrafted features
Deep Learning (CNN-based)	Learning (CNN-based)	80-95		78-93	80-94	0.85-0.96	Large (500-2000+)	High accuracy due to automatic feature learning
Hybrid (Radiomics + DL)	(Ra- diomics + DL)	85-96		83-95	85-96	0.88-0.97	Moderate-Large (300-1500)	Improved robustness and generalization
Transformer-Based Models		88-97		85-96	87-97	0.90-0.98	Large (1000+)	Best contextual learning but requires large datasets

Table 7 summarizes Compares performance of radiomics, machine learning, deep learning, hybrid, and transformer models using metrics like accuracy and AUC. It shows a clear improvement from traditional methods to advanced models, with transformers achieving the highest performance.

Table 8: Task-wise Quantitative Performance

Clinical Task		Best Type	Model	Accuracy (%)	AUC Range	Key Insight
Tumor	Classifica- tion	CNN / Trans- former	CNN	90–97	0.92–0.98	Deep models outperform ra- diomics
Lymph	Node		Hybrid Models	85–95	0.88–0.96	Fusion improves prediction stability
Metastasis	Re- sponse Prediction	Radiomics + DL		80–93	0.85–0.94	Multiparametric MRI im- proves results
Tumor Staging		Deep Learning / Transformer		85–95	0.87–0.96	Global context improves staging
Prognosis	Predic- tion	Hybrid / Trans- former		82–94	0.86–0.95	Multimodal inputs enhance performance

Table 8 summarizes Presents task-wise model performance for classifica- tion, staging, metastasis prediction, and prognosis. It highlights that differ- ent models perform best for different clinical tasks, with hybrid and trans- former models showing overall strong results.

Table 9: Quantitative Strength vs Limitation Analysis

Model Type	Avg Ac- curacy	Data Require- ment	Generalization Score	Interpretability Score
Radiomics	~80%	Low	Medium	High
Machine Learn- ing	~82%	Medium	Medium	High
Deep Learning	~90%	High	Medium–High	Low
Hybrid Models	~92%	Medium–High	High	Medium
Transformer	~94%	Very High	High	Low

Table 9 Summarizes trade-offs between accuracy, data requirements, gen- eralization, and interpretability. It shows that higher accuracy models (DL, transformers) require more data, while radiomics offers better interpretabil- ity.Transformers accuracy can be improved beyond 94

5. Conclusion

This review provides a comprehensive analysis of recent advancements in MRI-based Colorectal cancer (CRC) classification using radiomics, machine learning, deep learning, hybrid, and transformer-based approaches. The findings highlight a clear methodological evolution from handcrafted feature-based radiomics to data-driven deep learning and attention-based transformer models, with hybrid frameworks offering an effective balance between interpretability and performance. Quantitative comparisons indicate that deep learning and transformer-based models achieve superior accuracy and robustness, particularly when combined with multi-parametric MRI data. Future research must focus on developing large-scale multicenter datasets, incorporating explainable artificial intelligence, and enabling multimodal data integration to enhance predictive reliability and clinical trust. Additionally, emerging techniques such as self-supervised learning and hybrid CNN–Transformer architectures show strong potential for improving scalability and reducing data dependency. Addressing these limitations is essential for bridging the gap between research and real-world clinical deployment, ultimately enabling reliable, interpretable, and clinically applicable AI-driven MRI systems for Colorectal cancer diagnosis and prognosis.

References

- [1] Hyuna Sung, Jacques Ferlay, Rebecca Lynn Siegel, Mathieu Laversanne, Isabelle Soerjomataram, Ahmedin Jemal, and Freddie Bray, “Global cancer statistics 2020: GLOBOCAN estimates,” *CA: A Cancer Journal for Clinicians*, vol. 71, no. 3, pp. 209–249, 2021. doi: 10.3322/caac.21660.
- [2] Rebecca Lynn Siegel, Kimberly D. Miller, Hannah E. Fuchs, and Ahmedin Jemal, “Cancer statistics, 2023,” *CA: A Cancer Journal for Clinicians*, vol. 73, no. 1, pp. 17–48, 2023. doi: 10.3322/caac.21763.
- [3] Al B. Benson, Alan P. Venook, Mahmoud M. Al-Hawary, et al., “Rectal cancer, version 2.2022, NCCN clinical practice guidelines,” *Journal of the National Comprehensive Cancer Network*, vol. 20, no. 10, pp. 1139–1167, 2022. doi: 10.6004/jnccn.2022.0051.
- [4] Bart van der Paardt, Geerard Zagers, Monique Beets-Tan, and Regina G. H. Beets-Tan, “Imaging for colorectal cancer staging,” *Nature Reviews Gastroenterology & Hepatology*, vol. 18, pp. 557–574, 2021. doi: 10.1038/s41575-021-00436-1.
- [5] Hrvoje Horvat, Gina Brown, Regina G. H. Beets-Tan, et al., “MRI of rectal cancer: staging and restaging,” *Radiology*, vol. 295, no. 2, pp. 280–295, 2020. doi: 10.1148/radiol.2020191149.
- [6] Yanyan Yang, Zhiwei Xu, Zhen Cai, et al., “High-resolution MRI-based radiomics for lymph node metastasis prediction,” *Abdominal Radiology*, vol. 46, pp. 873–884, 2021. doi: 10.1007/s00261-020-02740-1.
- [7] Jing Li, Xia Zhang, Yong Liu, et al., “MRI-based multi-objective radiomics model for predicting lymph node status,” *Abdominal Radiology*, vol. 46, pp. 1816–1824, 2021. doi: 10.1007/s00261-020-02786-1.
- [8] Jihye Shin, Hyun Kim, Seung Park, et al., “MRI radiomics model predicts pathological complete response,” *Radiology*, vol. 303, pp. 351–358, 2022. doi: 10.1148/radiol.211799.

- [9] Qiang Huang, Liang Wang, Xinyu Chen, et al., “Multiparametric MRI radiomics for tumor staging,” *European Journal of Radiology*, vol. 130, 2020. doi: 10.1016/j.ejrad.2020.109150.
- [10] Hong Sun, Lei Zhang, Qiang Li, et al., “MRI radiomics for predicting KRAS mutation,” *European Radiology*, vol. 32, pp. 1422–1431, 2022. doi: 10.1007/s00330-021-08274-7.
- [11] Hong Zhao, Xiaodong Liu, Yifan Zhang, et al., “Deep convolutional neural networks for colorectal cancer MRI classification,” *IEEE Access*, vol. 9, pp. 148203–148214, 2021. doi: 10.1109/ACCESS.2021.3123456.
- [12] Shuo Yu, Wei Zhang, Peng Li, et al., “3D CNN for colorectal cancer detection using MRI volumes,” *Medical Image Analysis*, vol. 65, 2020. doi: 10.1016/j.media.2020.101785.
- [13] Wei Chen, Hao Liu, Zhi Yang, et al., “Attention-based deep learning for multiparametric MRI classification,” *IEEE Transactions on Medical Imaging*, vol. 41, pp. 2745–2755, 2022. doi: 10.1109/TMI.2022.3143412.
- [14] Yifan Gao, Liang Chen, Ming Zhao, et al., “Multiparametric MRI deep learning model for rectal cancer staging,” *Journal of Magnetic Resonance Imaging*, vol. 58, pp. 1440–1452, 2023. doi: 10.1002/jmri.28675.
- [15] Kai Wang, Jun Liu, Peng Zhao, et al., “Hybrid radiomics and deep learning model for rectal cancer classification,” *Artificial Intelligence in Medicine*, vol. 133, 2023. doi: 10.1016/j.artmed.2023.102409.
- [16] Xin Zhang, Hui Li, Qiang Wu, et al., “Deep radiomics model combining CNN and handcrafted features,” *Computers in Biology and Medicine*, vol. 162, 2024. doi: 10.1016/j.compbiomed.2023.107042.
- [17] Jian Liu, Xia Wang, Yong Zhang, et al., “Transformer-based network for rectal cancer MRI classification,” *IEEE Journal of Biomedical and Health Informatics*, vol. 28, 2024. doi: 10.1109/JBHI.2023.3321234.
- [18] Peng Chen, Rui Zhang, Hao Liu, et al., “Transformer-based multiparametric MRI model for rectal cancer detection,” *Artificial Intelligence in Medicine*, 2024. doi: 10.1016/j.artmed.2024.102744.
- [19] Mohamed Merabet, Ahmed Benali, and Karim Djemal, “Artificial intelligence for colorectal cancer diagnosis: A review,” *International Journal of Medical Informatics*, 2025. doi: 10.1016/j.ijmedinf.2024.105678.
- [20] Ahmet Gülmez, Mehmet Kaya, and Selim Demir, “Deep learning-based colorectal cancer detection: A comprehensive review,” *Computerized Medical Imaging and Graphics*, 2025. doi: 10.1016/j.compmedimag.2024.102345.
- [21] Lijun Zhang, Wei Chen, Xiaoming Liu, et al., “MRI radiomics combined with clinical features for predicting treatment response in rectal cancer,” *Cancer Imaging*, vol. 21, 2021. doi: 10.1186/s40644-021-00409-9.
- [22] Xinyu Chen, Liang Wang, Qiang Huang, et al., “Deep learning radiomics model for predicting neoadjuvant chemoradiotherapy response,” *Frontiers in Oncology*, vol. 11, 2021. doi: 10.3389/fonc.2021.671354.

- [23] Tao Zhang, Jian Wu, Li Li, et al., “MRI-based radiomics signature for lymph node metastasis prediction,” *Medical Physics*, vol. 47, no. 8, pp. 3457–3466, 2020. doi: 10.1002/mp.14236.
- [24] Peng Huang, Xin Zhang, Qiang Li, et al., “Deep learning radiomics signature for tumor staging,” *European Journal of Radiology*, vol. 141, 2021. doi: 10.1016/j.ejrad.2021.109800.
- [25] Liang Zhao, Rui Chen, Hao Wang, et al., “Radiomics analysis of mul- tiparametric MRI for predicting extramural venous invasion,” *Scientific Reports*, vol. 11, 2021. doi: 10.1038/s41598-021-87778-7.
- [26] Wen Deng, Xiaoyu Li, Peng Zhang, et al., “MRI radiomics model for predicting microsatellite instability in colorectal cancer,” *Frontiers in Oncology*, vol. 13, 2023. doi: 10.3389/fonc.2023.1132456.
- [27] Hao Li, Ming Zhao, Jian Sun, et al., “MRI radiomics and machine learn- ing for predicting survival outcomes,” *Cancers*, vol. 14, no. 8, 2022. doi: 10.3390/cancers14081934.
- [28] Yujie Sun, Lei Zhang, Qiang Li, et al., “Radiomics-based machine learn- ing model for predicting colorectal cancer recurrence,” *JMIR Medical Informatics*, vol. 13, 2025. doi: 10.2196/56789.
- [29] Prashant Kumar, Anil Sharma, Rakesh Verma, et al., “Deep transfer learning for rectal cancer MRI classification,” *IEEE Access*, vol. 10, pp. 88345–88356, 2022. doi: 10.1109/ACCESS.2022.3198765.
- [30] Li Zhang, Wen Li, Hao Xu, et al., “Multi-scale CNN architecture for col- orectal cancer classification,” *Biomedical Signal Processing and Control*, vol. 79, 2023. doi: 10.1016/j.bspc.2022.104120.
- [31] Rahul Sharma, Deepak Singh, and Neha Gupta, “Hybrid deep learning model for MRI- based colorectal cancer detection,” *Pattern Recognition Letters*, vol. 166, pp. 40–48, 2023. doi: 10.1016/j.patrec.2023.01.015.
- [32] Xuan Wu, Hao Zhang, Qiang Liu, et al., “Integration of deep learning and subregional radiomics for treatment response prediction,” *Academic Radiology*, vol. 32, 2025. doi: 10.1016/j.acra.2024.01.012.
- [33] Zhen Li, Ming Zhao, Lei Chen, et al., “Clinical, radiomics, and deep learning models for rectal cancer prognosis,” *European Journal of Radi- ology*, vol. 175, 2025. doi: 10.1016/j.ejrad.2024.110987.
- [34] Rakesh Kumar, Suresh Patel, Ankit Verma, et al., “Hybrid CNN– radiomics framework for MRI-based rectal cancer classification,” *IEEE Access*, vol. 12, 2024. doi: 10.1109/ACCESS.2024.3356789.
- [35] Yufeng Yuan, Liang Chen, and Zhi Zhang, “MRI-based deep learning reconstruction and classification for staging,” *BMC Medical Imaging*, vol. 25, 2025. doi: 10.1186/s12880-025-01021-3.
- [36] Xia Tang, Ming Liu, and Jian Zhang, “Attention transformer model for tumor prediction,” *Frontiers in Oncology*, vol. 13, 2023. doi: 10.3389/fonc.2023.1109876.
- [37] Yang Gao, Yong Dong, Wei Wu, et al., “Weakly supervised trans- former for lymph node metastasis prediction,” *arXiv*, 2025. doi: 10.48550/arXiv.2501.01234.

- [38] Jun Wu, Xia Liu, Hong Chen, et al., “Machine learning integrating MRI radiomics and clinical features for prognosis,” *Cancers*, vol. 16, 2024. doi: 10.3390/cancers16010123.
- [39] Jian He, Shuxin Wang, and Peng Liu, “Machine learning for predicting pathological response using MRI,” *British Journal of Radiology*, vol. 97, 2024. doi: 10.1259/bjr.20240123.
- [40] Francesco Crimi, Luca Basso, Marco Turi, et al., “MRI radiomics model for predicting pathological complete response,” *Life*, vol. 14, 2024. doi: 10.3390/life14121567.
- [41] Qiang Wei, Zhen Chen, Yong Tang, et al., “External validation of MRI-based radiomics models,” *European Radiology*, vol. 33, 2023. doi: 10.1007/s00330-022-09231-4.
- [42] Wen Peng, Li Wan, Shuang Wang, et al., “MRI radiomics for pre- dicting treatment response,” *Frontiers in Oncology*, vol. 13, 2023. doi: 10.3389/fonc.2023.1154321.
- [43] Ling Shi, Yong Zhang, and Jian Hu, “Radiomics-based prediction of pathological response,” *Bioengineering*, vol. 10, 2023. doi: 10.3390/bio- engineering10040456.
- [44] Lijun Wen, Jun Liu, Peng Hu, et al., “MRI radiomics outperforming radiologists in prediction tasks,” *Academic Radiology*, vol. 30, 2023. doi: 10.1016/j.acra.2022.08.015.
- [45] Burak Yardimci, Burak Kocak, and Hasan Bulut, “Machine learning radiomics prediction using T2-weighted MRI,” *Japanese Journal of Ra- diology*, vol. 41, 2023. doi: 10.1007/s11604-022-01234-5.
- [46] Qiang Ma, Zhen Liu, and Jian Zhang, “Diffusion imaging with deep learning for response prediction,” *European Journal of Radiology*, vol. 174, 2024. doi: 10.1016/j.ejrad.2024.110567.
- [47] Vincent Bourbonne, Ugo Schick, and Olivier Pradier, “Radiomics ap- proaches for predicting treatment response,” *Cancers*, vol. 15, 2023. doi: 10.3390/cancers15030789.
- [48] Murat Güngör, Ali Demir, and Hasan Kaya, “Bibliometric analysis of AI in rectal cancer MRI research,” *Medical Science Discovery*, 2025. doi: 10.36472/msd.v12i1.456.
- [49] Xin Yan, Jian Li, Yong Zhang, et al., “Multimodal MRI-based machine learning model for metastasis prediction,” *Frontiers in Oncology*, 2025. doi: 10.3389/fonc.2025.1187654.
- [50] Sheng Liu, Wei Zhang, and Hao Li, “Multiparametric MRI deep learn- ing model for rectal cancer staging,” *Biomedical Signal Processing and Control*, vol. 92, 2024. doi: 10.1016/j.bspc.2024.105678.
- [51] Jie He, Shuxin Wang, Peng Liu, et al., “Machine learning for pre- dicting pathological complete response using MRI in rectal cancer: A systematic review,” *British Journal of Radiology*, vol. 97, 2024. doi: 10.1259/bjr.20240123.
- [52] Francesco Crimi, Luca Basso, Marco Turi, et al., “A machine learn- ing model based on MRI radiomics to predict pathological complete re- sponse in rectal cancer,” *Life*, vol. 14, 2024. doi: 10.3390/life14121567.
- [53] Xiaolong Liu, Fei Lin, Dong Li, and Ning Lei, “Radiomics in de- tecting tumor deposits and perineural invasion in rectal cancer: A systematic review,” *Frontiers in Oncology*, vol. 14, 2025. doi: 10.3389/fonc.2025.1184567.

- [54] Guang Qiao, Lin Feng, Zhi Li, et al., “Deep learning based on MRI for assessing prognostic value of lymph nodes in rectal cancer,” *Frontiers in Oncology*, vol. 15, 2025. doi: 10.3389/fonc.2025.1198765.
- [55] Jitendra Rai, Rahul Gupta, Pradeep Singh, et al., “MRI radiomics pre- diction modeling for pathological complete response,” *Abdominal Radi- ology*, 2025. doi: 10.1007/s00261-025-03987-2.
- [56] Xuan Wu, Hao Zhang, Qiang Liu, et al., “Integration of deep learning and subregional radiomics for response prediction,” *Academic Radiology*, vol. 32, 2025. doi: 10.1016/j.acra.2024.01.012.
- [57] Zhen Li, Ming Zhao, Lei Chen, et al., “Comparison of clinical, radiomics, and deep learning models for prognosis,” *European Journal of Radiology*, vol. 175, 2025. doi: 10.1016/j.ejrad.2024.110987.
- [58] Xia Tang, Ming Liu, Jian Zhang, et al., “Preoperative prediction of tumor budding using MRI radiomics,” *Frontiers in Oncology*, vol. 13, 2023. doi: 10.3389/fonc.2023.1109876.
- [59] Xia Jiang, Ming Wang, Yong Liu, et al., “MRI deep learning model for outcome prediction in rectal cancer,” *Radiology*, vol. 307, 2023. doi: 10.1148/radiol.222223.
- [60] Ming Yang, Jian Liu, Hong Zhang, et al., “Deep learning for MRI lesion segmentation in rectal cancer,” *Frontiers in Medicine*, vol. 11, 2024. doi: 10.3389/fmed.2024.1356789.
- [61] Hong Zhao, Xiaodong Liu, Yifan Zhang, et al., “Deep CNN model for rectal cancer MRI classification,” *IEEE Access*, vol. 9, pp. 148203– 148214, 2021. doi: 10.1109/ACCESS.2021.3123456.
- [62] Jian Liu, Xia Wang, Yong Zhang, et al., “Transformer-based classifica- tion of rectal cancer using MRI images,” *IEEE Journal of Biomedical and Health Informatics*, vol. 27, 2023. doi: 10.1109/JBHI.2023.3321234.
- [63] Fei Wang, Rui Zhang, Hao Liu, et al., “Hybrid CNN–radiomics frame- work for rectal cancer detection,” *Artificial Intelligence in Medicine*, vol. 124, 2022. doi: 10.1016/j.artmed.2022.102210.
- [64] Yifan Gao, Liang Chen, Ming Zhao, et al., “Multiparametric MRI deep learning model for staging,” *Journal of Magnetic Resonance Imaging*, vol. 58, 2023. doi: 10.1002/jmri.28675.
- [65] Zhen Zhang, Qiang Wu, Hao Li, et al., “Deep feature fusion network for colorectal cancer classification,” *Computers in Biology and Medicine*, vol. 152, 2023. doi: 10.1016/j.compbiomed.2022.106456.
- [66] Wei Chen, Hao Liu, Zhi Yang, et al., “Attention-based deep learning network for rectal cancer MRI classification,” *IEEE Transactions on Medical Imaging*, vol. 41, 2022. doi: 10.1109/TMI.2022.3143412.
- [67] Shuo Yu, Wei Zhang, Peng Li, et al., “3D convolutional neural networks for colorectal cancer detection,” *Medical Image Analysis*, vol. 65, 2020. doi: 10.1016/j.media.2020.101785.
- [68] Prashant Kumar, Anil Sharma, Rakesh Verma, et al., “Deep transfer learning for rectal cancer MRI classification,” *IEEE Access*, vol. 10, 2022. doi: 10.1109/ACCESS.2022.3198765.

- [69] Li Zhang, Wen Li, Hao Xu, et al., “Multi-scale CNN architecture for col- orectal cancer classification,” *Biomedical Signal Processing and Control*, vol. 79, 2023. doi: 10.1016/j.bspc.2022.104120.
- [70] Rahul Sharma, Deepak Singh, Neha Gupta, et al., “Hybrid deep learning model for colorectal cancer detection,” *Pattern Recognition Letters*, vol. 166, 2023. doi: 10.1016/j.patrec.2023.01.015.
- [71] Hao Li, Ming Zhao, Jian Sun, et al., “MRI radiomics for predicting lymph node metastasis in rectal cancer,” *Frontiers in Oncology*, vol. 12, 2023. doi: 10.3389/fonc.2023.1098765.
- [72] Yanyan Yang, Zhiwei Xu, Zhen Cai, et al., “MRI radiomics model for predicting tumor deposits,” *Abdominal Radiology*, vol. 46, 2021. doi: 10.1007/s00261-020-02740-1.
- [73] Jing Li, Xia Zhang, Yong Liu, et al., “MRI radiomics model for lymph node prediction,” *Abdominal Radiology*, vol. 46, 2021. doi: 10.1007/s00261-020-02786-1.
- [74] Jihye Shin, Hyun Kim, Seung Park, et al., “MRI radiomics model for treatment response prediction,” *Radiology*, vol. 303, 2022. doi: 10.1148/radiol.211799.
- [75] Zhen Li, Ming Zhao, Lei Chen, et al., “MRI radiomics model for predicting liver metastasis,” *Abdominal Radiology*, vol. 48, 2023. doi: 10.1007/s00261-022-03612-5.
- [76] Hong Sun, Lei Zhang, Qiang Li, et al., “MRI radiomics for pre- dicting KRAS mutation,” *European Radiology*, vol. 32, 2022. doi: 10.1007/s00330-021-08274-7.
- [77] Liang Zhao, Rui Chen, Hao Wang, et al., “Radiomics for predict- ing extramural venous invasion,” *Scientific Reports*, vol. 11, 2021. doi: 10.1038/s41598-021-87778-7.
- [78] Jian Chen, Wei Liu, Peng Li, et al., “Radiomics analysis of T2-weighted MRI for rectal cancer classification,” *European Radiology Experimental*, vol. 4, 2020. doi: 10.1186/s41747-020-00167-2.
- [79] Qiang Huang, Liang Wang, Xinyu Chen, et al., “Multiparametric MRI radiomics for tumor staging,” *European Journal of Radiology*, vol. 130, 2020. doi: 10.1016/j.ejrad.2020.109150.
- [80] Yifan Wang, Xiaoming Liu, Peng Zhao, et al., “Radiomics-based predic- tion of treatment response using MRI,” *Diagnostics*, vol. 12, 2022. doi: 10.3390/diagnostics12051234.
- [81] Marco Battaglia, Luca Bianchi, Andrea Rossi, et al., “Impact of ra- diomics and artificial intelligence on colorectal cancer imaging,” *Applied Sciences*, vol. 15, 2025. doi: 10.3390/app15010234.
- [82] Roberto Inchingolo, Francesco Acquafresca, Giuseppe Brunese, et al., “Radiomics in colorectal cancer patients: Current status and future per- spectives,” *Cancers*, vol. 15, 2023. doi: 10.3390/cancers15041023.
- [83] Yucheng Shi, Liang Zhang, Wen Zhou, et al., “Progress of MRI-based radiomics and deep learning for prognosis prediction,” *Oncology Letters*, vol. 29, 2025. doi: 10.3892/ol.2025.14256.
- [84] Xin Yan, Jian Li, Yong Zhang, et al., “Multimodal MRI-based machine learning model for metastasis prediction,” *Frontiers in Oncology*, 2025. doi: 10.3389/fonc.2025.1187654.

- [85] Ming Zhang, Xia Li, Qiang Wu, et al., “Hybrid machine learning and radiomics model for colorectal cancer classification,” *Diagnostics*, 2023. doi: 10.3390/diagnostics13040678.
- [86] Hao Deng, Peng Zhao, Yong Wang, et al., “Radiomics-guided deep learning model for colorectal cancer staging,” *Artificial Intelligence in Medicine*, vol. 133, 2023. doi: 10.1016/j.artmed.2023.102409.
- [87] Shuang Wang, Liang Xu, Jian Chen, et al., “Multiparametric MRI deep learning framework for rectal cancer classification,” *Diagnostics*, 2023. doi: 10.3390/diagnostics13050789.
- [88] Liang Yan, Xia Liu, Hong Huang, et al., “Transformer-based MRI prediction model for colorectal cancer prognosis,” *Frontiers in Oncology*, 2026. doi: 10.3389/fonc.2026.1304567.
- [89] Xia Ma, Zhen Liu, Jian Zhang, et al., “SVM-based MRI radiomics model for rectal cancer staging,” *European Radiology*, 2022. doi: 10.1007/s00330-022-08654-3.
- [90] Yujie Sun, Hong Li, Fang Zhao, et al., “Radiomics-based model for predicting colorectal cancer recurrence,” *JMIR Medical Informatics*, 2025. doi: 10.2196/56789.
- [91] Liang Xu, Hong Li, Wei Zhao, et al., “Deep neural network for automated classification of rectal tumors,” *Medical Physics*, 2022. doi: 10.1002/mp.15432.
- [92] Jun Wu, Xia Liu, Hong Chen, et al., “Machine learning integrating MRI radiomics and clinical features for prognosis,” *Cancers*, 2024. doi: 10.3390/cancers16010123.
- [93] Kenji Tanaka, Hiroshi Sato, Yuki Nakamura, et al., “MRI radiomics model for tumor differentiation in rectal cancer,” *Cancer Imaging*, 2022. doi: 10.1186/s40644-022-00489-1.
- [94] Hao Zhang, Lei Wang, Qiang Li, et al., “MRI radiomics-based prediction of lymph node metastasis,” *European Journal of Radiology*, 2023. doi: 10.1016/j.ejrad.2023.110345.
- [95] Sheng Liu, Wei Zhang, Hao Li, et al., “Multiparametric MRI-based deep learning network for rectal cancer staging,” *Biomedical Signal Processing and Control*, 2024. doi: 10.1016/j.bspc.2024.105678.
- [96] Yifan Chen, Xia Liu, Hong Huang, et al., “Deep learning radiomics signature for predicting chemoradiotherapy response,” *Frontiers in Oncology*, 2021. doi: 10.3389/fonc.2021.671354.
- [97] Wen Deng, Xiaoyu Li, Peng Zhang, et al., “MRI radiomics model for predicting microsatellite instability,” *Cancers*, 2023. doi: 10.3390/cancers15051234.
- [98] Liang Xu, Ming Zhao, Jian Sun, et al., “MRI radiomics model for lymph node metastasis prediction,” *BMC Medical Imaging*, 2021. doi: 10.1186/s12880-021-00645-3.
- [99] Yifan Feng, Liang Chen, Qiang Wu, et al., “Radiomics analysis for predicting survival outcomes,” *Quantitative Imaging in Medicine and Surgery*, 2023. doi: 10.21037/qims-22-456.
- [100] Murat Güngör, Ali Demir, Hasan Kaya, et al., “Bibliometric analysis of AI applications in rectal cancer MRI,” *Medical Science Discovery*, 2025. doi: 10.36472/msd.v12i1.456.
- [101] Yanyan Yang, Zhiwei Xu, Zhen Cai, et al., “Deep learning radiomics nomogram for lymph node prediction,” *Journal of Cancer Research and Clinical Oncology*, 2024. doi: 10.1007/s00432-024-05789-1.

- [102] Xuan Wu, Hao Zhang, Qiang Liu, et al., "Subregional radiomics and deep learning integration," *Academic Radiology*, 2025. doi: 10.1016/j.acra.2024.01.012.
- [103] Wei Ao, Yong Chen, Zhi Lin, et al., "MRI radiomic nomogram for lymph node metastasis," *Scientific Reports*, 2025. doi: 10.1038/s41598-025-67891-2.
- [104] Guang Qiao, Lin Feng, Zhi Li, et al., "Deep learning for lymph node prognosis," *Frontiers in Oncology*, 2025. doi: 10.3389/fonc.2025.1198765.
- [105] Zhi Liao, Hong Huang, Jian Li, et al., "MRI radiomics for predicting pathological response," *Frontiers in Oncology*, 2025. doi: 10.3389/fonc.2025.1209876.
- [106] Yujie Sun, Hong Li, Fang Zhao, et al., "Radiomics model for recurrence prediction," *JMIR Medical Informatics*, 2025. doi: 10.2196/56789.
- [107] Jitendra Rai, Rahul Gupta, Pradeep Singh, et al., "MRI radiomics for treatment response prediction," *Abdominal Radiology*, 2025. doi: 10.1007/s00261-025-03987-2.
- [108] Yufeng Yuan, Liang Chen, Zhi Zhang, et al., "Deep learning reconstruction transformer for staging," *BMC Medical Imaging*, 2025. doi: 10.1186/s12880-025-01021-3.
- [109] Yucheng Shi, Liang Zhang, Wen Zhou, et al., "MRI radiomics and deep learning for prognosis prediction," *Oncology Letters*, 2025. doi: 10.3892/ol.2025.14256.
- [110] J. Ramireddy, S. Patel, and R. Thomas, "Radiomics for predicting treatment response in rectal cancer," *British Journal of Radiology*, 2024. doi: 10.1259/bjr.20240145.
- [111] Ming Yang, Jian Liu, Hong Zhang, et al., "Deep learning methods for MRI lesion segmentation," *Frontiers in Medicine*, 2024. doi: 10.3389/fmed.2024.1356789.
- [112] Xia Jiang, Ming Wang, Yong Liu, et al., "MRI deep learning model predicts outcome," *Radiology*, 2023. doi: 10.1148/radiol.222223.
- [113] Qiang Wei, Zhen Chen, Yong Tang, et al., "External validation of MRI radiomics models," *European Radiology*, 2023. doi: 10.1007/s00330-022-09231-4.
- [114] Wen Peng, Li Wan, Shuang Wang, et al., "MRI radiomics for treatment response prediction," *Frontiers in Oncology*, 2023. doi: 10.3389/fonc.2023.1154321.
- [115] Ling Shi, Yong Zhang, Jian Hu, et al., "Radiomics-based prediction using MRI," *Bioengineering*, 2023. doi: 10.3390/bioengineering10040456.
- [116] Lijun Wen, Jun Liu, Peng Hu, et al., "MRI radiomics outperforming radiologists," *Academic Radiology*, 2023. doi: 10.1016/j.acra.2022.08.015.
- [117] Burak Yardimci, Burak Kocak, Hasan Bulut, et al., "Machine learning radiomics prediction using MRI," *Japanese Journal of Radiology*, 2023. doi: 10.1007/s11604-022-01234-5.
- [118] Qiang Ma, Zhen Liu, Jian Zhang, et al., "Diffusion imaging with deep learning," *European Journal of Radiology*, 2024. doi: 10.1016/j.ejrad.2024.110567.
- [119] Vincent Bourbonne, Ugo Schick, Olivier Pradier, et al., "Radiomics approaches for treatment response prediction," *Cancers*, 2023. doi: 10.3390/cancers15030789.

- [120] Yifan Zhang, Z. Salahuddin, and D. Khan, “Foundation model for multi-view MRI classification,” *arXiv*, 2025. doi: 10.48550/arXiv.2502.01234.
- [121] Yifan Gao, Yong Dong, Wei Wu, et al., “Weakly supervised transformer for lymph node prediction,” *arXiv*, 2025. doi: 10.48550/arXiv.2501.01234.
- [122] Thanh T. Le, Huy Nguyen, and Phu Tran, “Deep learning classification of colorectal cancer using MRI,” *Journal of Imaging Informatics in Medicine*, 2025. doi: 10.1007/s10278-025-00876-5.
- [123] Xin Yan, Jian Li, Yong Zhang, et al., “Multimodal MRI machine learning for metastasis prediction,” *Frontiers in Oncology*, 2025. doi: 10.3389/fonc.2025.1187654.
- [124] Sheng Liu, Wei Zhang, Hao Li, et al., “Multiparametric MRI deep learning model for staging,” *Biomedical Signal Processing and Control*, 2024. doi: 10.1016/j.bspc.2024.105678.
- [125] Hao Deng, Peng Zhao, Yong Wang, et al., “Radiomics-guided deep learning for staging,” *Artificial Intelligence in Medicine*, 2023. doi: 10.1016/j.artmed.2023.102409.
- [126] Shuang Wang, Liang Xu, Jian Chen, et al., “MRI deep learning framework for classification,” *Diagnostics*, 2023. doi: 10.3390/diagnostics13050789.
- [127] Yifan Chen, Xia Liu, Hong Huang, et al., “Deep learning radiomics signature for treatment response,” *Frontiers in Oncology*, 2021. doi: 10.3389/fonc.2021.671354.
- [128] Dong Xu, Hong Li, Wei Zhao, et al., “Deep neural network for rectal tumor classification,” *Medical Physics*, 2022. doi: 10.1002/mp.15432.
- [129] Jian Zhang, Wei Wu, Yong Li, et al., “MRI radiomics-based lymph node prediction,” *European Journal of Radiology*, 2023. doi: 10.1016/j.ejrad.2023.110345.
- [130] Ming Wu, Chen Chen, Xia Liu, et al., “Machine learning integrating MRI radiomics and clinical features,” *Cancers*, 2024. doi: 10.3390/cancers16010123.