A Design Distributed and fair beaconing congestion control in vehicular network

[1]Ms. More Rani, [2]Ms. Pansare Tejashwi, [3]Ms.Waghmode Madhuri, [4]Mr.Bandgar S.B

S.B.patil college of engineering,indapur

***ABSTRACT*— A DISTRIBUTED SYSTEM IS A COLLECTION OF INDEPENDENT COMPUTERS THAT PRESENT TO ITS USERS AS A SINGLE SYSTEM. COOPERATIVE INTER-VEHICULAR APPLICATIONS LOOK ON THE EXCHANGE OF BROADCAST SINGLE-HOP STATUS MESSAGES ENCOMPASSED BY VEHICLES, CALLED BEACONS. MAIN AIM OF THAT SYSTEM FIND OUT TRAFFIC ON ROAD LOW, HIGH, MEDIUM.**

Inter-vehicle communications based on wireless technologies surface the way for innovative applications in traffic safety, driver-assistance, traffic control and other advanced services which will make up future. Control of the traffic of each vehicle. By using it as a layering as optimized decomposition problem (NUM). This allows us to formally apply the notion of fairness of a beaconing rate allocation in vehicular networks and to control the trade-off between efficiency and fairness. The layering as optimized decomposition methodology provides a right framework to design a broad family of simple and decentralized algorithms, with proved convergence guarantees to a fair allocation solution it provides a mathematical framework to develop decentralized and simple algorithms. The Fair Adaptive Beaconing Rate for Inter vehicular Communications (FABRIC) algorithm. FABRIC, is a decentralized rate allocation algorithm with theoretical and empirical convergence properties, which requires limited signaling overhead between vehicles.

***Index Terms*— Vehicular Communications Beaconing congestion control Rate control, Fairness Network Utility Maximization**

I. *INTRODUCTION*

The goal is to limit the channel bandwidth used by beacons to ensure that the remaining capacity is available to event-based messages. A distributed system is a collection of independent computers that present to its users as a single system.. Cooperative inter-vehicular applications look on the exchange of broadcast single-hop status messages encompassed by vehicles, called beacons. Control the unwanted message between the vehicles. optimizing the transmission of warning messages is based on the observation that messages should be repeatedly sent out until the abnormal[behavior stops and the vehicle returns to abnormal behavior. The layering as optimized decomposition methodology provides a right framework to design a broad family of simple and decentralized algorithms, with proved convergence guarantees to a fair allocation solution it provides a mathematical framework to develop decentralized and simple algorithms. Message sent when- ever a vehicle shows an abnormal behavior (e.g., it broke down and is blocking the road/lane, or it lost control and it is changing lanes unexpectedly).FABRIC, is a decentralized rate allocation algorithm with theoretical and empirical convergence properties, which requires limited signaling overhead between vehicles. minimize the traffic on the road by using IR sensor display the traffic high, low, medium. emergency warning messages can be served and delivered by the system with limited delay.one lane incoming the ambulance then another lane automatically stop particular time.

Mathematical model

Mathematical formulation

Let S be the set of activities
I = CM, Ru.in,Tr.in2,R.in,Rd.in, Po.in1, Po.in2, Sp.in, T.in
Where,
CM=Corrective action by school management
Ru.in1=_find route
Tr.in=Traffic Detected
Rd.in=message to user or driver.
Po.in1=Position detected
Po.in2=message send to user or driver
Sp.in=Speed control
T.in=successful journey
Q=q0, q1, q2, q3, q4, q5, q6, q7, qf
q0= Initial state
q1= find route
q2= traffic not detected detected
q3= message to user or driver
q4= route detected
q5= position detected

q5= Speed control
qf= Successful journey
qf=Q*I
Q= Valid state
I= Valid input
qf= Successful journey



Block Diagram:



II. ***ACKNOWLEDGMENT***

It gives us great pleasure in presenting the preliminary project report on `a Design Distributed and Fair Beaconing Rate Congestion Control in Vehicular Networks' .I would like to take this opportunity to thank my internal guide Prof.S.B.Bandgar for giving me all the help and guidance I needed. I am really grateful to them for their kind support. Their valuable suggestions were very helpful.

REFERENCES

[1]Base paper-Distributed and Fair Beaconing Rate Adaptation for Congestion Control in Vehicular Networks.
[2] H. Hartenstein and K. P. Laberteaux, VANET. Vehicular Application and Inter-Networking Technologies, Wiley, 2010.
[3]ETSI EN 302 663, Intelligent Transport Systems (ITS); Access layer specification for Intelligent Transport Systems operating in the 5 GHz frequency band, V0.1.3, 2012
[4]G. Karagiannis, O. Altintas, E. Ekici, G. Heijenk, B. Jarupan, K. Lin, and T. Weil, Vehicular Networking: A Survey and Tutorial on Requirements,Architectures, Challenges, Standards and Solutions, IEEE Communications Surveys Tutorials, vol. 13, no. 4, pp. 584-616,2011.
[5] ETSI EN 302 637-2, Intelligent Transportation Systems (ITS); Vehicular Communications; Basic Set of Applications; Part 2: Speci_cation of Cooperative Awareness Basic Service, 2013
[6] M. Sepulcre, J. Mittag, P. Santi, H. Hartenstein, and J. Gozalvez, Conges- tion and Awareness Control in Cooperative Vehicular Systems, Proceedings of the IEEE, vol. 99, no. 7, pp. 1260-1279, 2014
[7] K, Tian Lan, M. Chiang, A. Sabharwal, An Axiomatic Theory of Fairness in Network Resource Allocation, Proceedings IEEEINFOCOM, pp.19, 2010